



TECHNICAL DATA SHEET

POWERFULL - P 210 SS (rev. 001)

GEN SET PERFORMANCE

Continuous power (P.R.P.):	208,00 kVA
Continuous power (P.R.P.):	166,40 kW
Stand-by power (L.T.P.):	229,00 kVA
Stand-by power (L.T.P.):	183,20 kW
cos(φ):	0.8
Frequency:	50 Hz
Voltage:	400/230 V
No. phases:	three-phases w neutral
Engine speed:	1500 rpm
Length:	4080 mm
Width:	1320 mm
Height:	2550 mm
Weight:	3205 kg



ENGINE

Brand:	PERKINS
Model:	1306CE87TAG3
No. of Cylinders:	6
Cubic capacity:	8,7 l
Air intake:	Turbocharged
Cooling:	water
Flywheel net power:	180 kW
Fuel cons. at 100% (L.T.P.):	49,1 l/h
Fuel cons. at 100% (P.R.P.):	45,2 l/h
Fuel cons. at 75% (P.R.P.):	35 l/h
Fuel cons. at 50% (P.R.P.):	24 l/h
Fuel cons. at 25% (P.R.P.):	N/A

BASE FRAME

Model:	ST40S/20
Tank Capacity:	270 l
Canopy:	C40

CONTROL PANEL

Available versions:	PW005
	EVMAN
	EVMAN + AUTOSTART
	EVAU
	EVAU + ATS
	IN SYNC

ALTERNATOR

Brand:	MARELLI
Model:	MJB250LA4
Continuous power:	220 kVA
Stand-by power:	240 kVA
Connection:	Stella serie

STARTING BATTERY

Capacity:	120 Ah
Quantity:	2
Voltage:	24 V

EXHAUST SILENCER

Model:	MSR/a 100
Quantity:	1
Diameter:	114 mm

FLEXIBLE PIPE

Model:	DN100
Quantity:	1
Diameter:	114 mm

Standard reference conditions 25 °C temperature, altitude 1-1000 mt. A.S.L., R. humidity 30%, atmospheric pressure 100 kPa (1 bar), power factor 0.8 lag, load balanced - non distortional. The mentioned power values are according to **ISO8528-1 standards**